

Running soapUI Script on Linux

Symptom

The soapUI script only works on CDP Servers installed on Windows.

When executed on a Linux CDP Server, the script fails on Volume and Disk Safe creation due to the path, e.g., C:\SOAPDiskSafeTest1.

XML Errors:

```
<faultstring>Path must be absolute</faultstring>  
<faultstring>Invalid Path.</faultstring>
```

Resolution

If you want the scripts to work "out of the box," use the following credentials:

- username: admin
- password: admin

In order to make the soapUI script work on Linux CDP Servers, edit the Volume Path in the createVolume calls, and also change the Disk Safe path in the createDiskSafe calls.

Related Articles

Page: [Accessing API Documentation \(CDP\)](#) Labels: [enterprise_edition](#), [advanced_edition](#), [standard_edition](#), [api](#)

Page: [Accessing Example API Functions \(CDP\)](#) Labels: [enterprise_edition](#), [standard_edition](#), [advanced_edition](#), [api](#)

Page: [Running soapUI Script on Linux \(CDP\)](#) Labels: [api](#)

Page: [API - Solved Issue with Closed Disk Safe \(CDP\)](#) Labels: [api](#)

Page: [API - Solved Issue with Wrong User Attributes Keys when Creating and Getting Power Users \(CDP\)](#) Labels: [api](#)

Page: [API - Solved Issue with createPolicy \(CDP\)](#) Labels: [api](#)

Page: [API - Solved Issue with getStorageDiskByPath \(CDP\)](#) Labels: [api](#)