Running soapUI Script on Linux

Symptom

The soapUI script only works on CDP Servers installed on Windows.

When executed on a Linux CDP Server, the script fails on Volume and Disk Safe creation due to the path, e.g., `C:\SOAPDiskSafeTest1`.

XML Errors:

```
<faultstring>Path must be absolute</faultstring>
<faultstring>Invalid Path.</faultstring>
```

Resolution

If you want the scripts to work "out of the box," use the following credentials:

- username: admin
- password: admin

In order to make the soapUI script work on Linux CDP Servers, edit the Volume Path in the `createVolume` calls, and also change the Disk Safe path in the `createDiskSafe` calls.

Related Articles

Page: Accessing API Documentation (CDP) Labels: enterprise_edition, advanced_edition, standard_edition, api

Page: Accessing Example API Functions (CDP) Labels: enterprise_edition, standard_edition, advanced_edition, api

Page: Running soapUI Script on Linux (CDP) Labels: api

Page: API - Solved Issue with Closed Disk Safe (CDP) Labels: api

Page: API - Solved Issue with Wrong User Attributes Keys when Creating and Getting Power Users (CDP) Labels: api

Page: API - Solved Issue with createPolicy (CDP) Labels: api

Page: API - Solved Issue with getStorageDiskByPath (CDP) Labels: api