

Installing Agent on CentOS, RHE and Fedora

1. Installing Agent Using YUM | 2. Install Agent Manually (Using RPM) | 3. Install CDP Linux Device Driver

1. Installing Agent Using YUM

1.1 Configure YUM Repository

YUM is the easiest way to keep programs up-to-date on RedHat-compatible distributions. It downloads and installs the latest version of a program. You should configure the YUM repository to manage install and [upgrades](#) of CDP Agent.

First, create a YUM `.repo` file with the R1Soft repository information. Save the file in the `yum.repos.d` directory which is typically located in `/etc/`.

1. Open the new file with a text editor such as `vi` or `nano`:

```
# cd /etc/yum.repos.d
# vi r1soft.repo
```

or

```
# nano -w /etc/yum.repos.d/r1soft.repo
```

```
[root@centos-server ~]# nano -w /etc/yum.repos.d/r1soft.repo
```

2. Insert the following text into the file and save the file:

```
[r1soft]
name=R1Soft Repository Server
baseurl=http://repo.r1soft.com/yum/stable/$basearch/
enabled=1
gpgcheck=0
```

```

GNU nano 2.0.9 File: /etc/yum.repos.d/r1soft.repo
[r1soft]
name=R1Soft Repository Server
baseurl=http://repo.r1soft.com/yum/stable/$basearch/
enabled=1
gpgcheck=0

```

3. To verify what is written to the file, use the following command:

```
# cat /etc/yum/yum.repos.d/r1soft.repo
```

```

[root@centos-server ~]# cat /etc/yum.repos.d/r1soft.repo
[r1soft]
name=R1Soft Repository Server
baseurl=http://repo.r1soft.com/yum/stable/$basearch/
enabled=1
gpgcheck=0

```

1.2 Install the Package

Once you have configured the YUM repository, you can use the following command to install CDP Agent:

```
# yum install r1soft-cdp-enterprise-agent
```

```
[root@centos-server cdp]# yum install r1soft-cdp-enterprise-agent
Loaded plugins: fastestmirror, presto
Loading mirror speeds from cached hostfile
 * base: centos.itt-consulting.com
 * extras: centos.itt-consulting.com
 * updates: centos.itt-consulting.com
Setting up Install Process
Resolving Dependencies
--> Running transaction check
---> Package r1soft-cdp-enterprise-agent.i386 0:4.2.0-17723 will be installed
--> Processing Dependency: r1soft-cdp-agent >= 4.2.0 for package: r1soft-cdp-enterprise-agent-4.2.0-17723.i386
--> Processing Dependency: r1soft-setup >= 4.2.0 for package: r1soft-cdp-enterprise-agent-4.2.0-17723.i386
--> Running transaction check
---> Package r1soft-cdp-agent.i386 0:4.2.0-17723 will be installed
--> Processing Dependency: r1soft-cdp-async-agent-2-6 >= 4.2.0 for package: r1soft-cdp-agent-4.2.0-17723.i386
---> Package r1soft-setup.i386 0:4.2.0-17723 will be installed
--> Running transaction check
---> Package r1soft-cdp-async-agent-2-6.i386 0:4.2.0-17723 will be installed
--> Finished Dependency Resolution

Dependencies Resolved

=====
Package                               Arch      Version      Repository    Size
=====
Installing:
r1soft-cdp-enterprise-agent           i386      4.2.0-17723  r1soft        2.5 k
Installing for dependencies:
r1soft-cdp-agent                       i386      4.2.0-17723  r1soft        4.6 M
r1soft-cdp-async-agent-2-6            i386      4.2.0-17723  r1soft        13 M
r1soft-setup                           i386      4.2.0-17723  r1soft        688 k

Transaction Summary
=====
Install      4 Package(s)

Total download size: 19 M
Installed size: 52 M
Is this ok [y/N]: y
```

Then, enter "y" to install all the dependencies of the package.

```

Is this ok [y/N]: y
Downloading Packages:
Setting up and reading Presto delta metadata
Processing delta metadata
Package(s) data still to download: 19 M
(1/4): r1soft-cdp-agent-4.2.0.i386.rpm | 4.6 MB 00:23
(2/4): r1soft-cdp-async-agent-2-6-4.2.0.i386.rpm | 13 MB 01:13
(3/4): r1soft-cdp-enterprise-agent-4.2.0.i386.rpm | 2.5 kB 00:00
(4/4): r1soft-setup-4.2.0.i386.rpm | 688 kB 00:05
-----
Total 185 kB/s | 19 MB 01:43
Running rpm_check_debug
Running Transaction Test
Transaction Test Succeeded
Running Transaction
  Installing : r1soft-setup-4.2.0-17723.i386 1/4
  Installing : r1soft-cdp-async-agent-2-6-4.2.0-17723.i386 2/4
  Installing : r1soft-cdp-agent-4.2.0-17723.i386 3/4
/etc/init.d/cdp-agent stop: cdp (no pid file) not running
Attempting to get a kernel module from 'krnlbld.r1soft.com'

No binary module was found for your kernel. The kernel headers will be required
to build a module. See '/usr/bin/r1soft-setup --help' for more information
/etc/init.d/cdp-agent start: cdp started
  Installing : r1soft-cdp-enterprise-agent-4.2.0-17723.i386 4/4

Installed:
  r1soft-cdp-enterprise-agent.i386 0:4.2.0-17723

Dependency Installed:
  r1soft-cdp-agent.i386 0:4.2.0-17723
  r1soft-cdp-async-agent-2-6.i386 0:4.2.0-17723
  r1soft-setup.i386 0:4.2.0-17723

Complete!

```

2. Install Agent Manually (Using RPM)

2.1 Download CDP Agent

See [Obtaining Linux CDP Enterprise Agent](#).

2.2 Make Sure You Can Unzip the Download

Most Linux distributions come with the unzip utility pre-installed. To determine if you have the unzip utility, run:

```
# which unzip
```

This should return an output similar to the following:

```
# which unzip
/usr/bin/unzip
```

```
[root@centos-server ~]# which unzip
/usr/bin/unzip
```

If it returns the following output, you need to install the unzip utility first:

```
unzip: Command not found.
```

To install unzip on RHE, CentOS, and Fedora:

```
# yum install unzip
```

```
[root@centos-server ~]# yum install unzip
Loaded plugins: fastestmirror
Loading mirror speeds from cached hostfile
 * base: centos.itt-consulting.com
 * extras: centos.itt-consulting.com
 * updates: centos.itt-consulting.com
base | 3.7 kB | 00:00
extras | 3.5 kB | 00:00
extras/primary_db | 6.3 kB | 00:00
updates | 3.5 kB | 00:00
updates/primary_db | 1.1 MB | 00:00
Setting up Install Process
Resolving Dependencies
--> Running transaction check
---> Package unzip.x86_64 0:6.0-1.el6 set to be updated
--> Finished Dependency Resolution

Dependencies Resolved

=====
Package Arch Version Repository Size
=====
Installing:
unzip x86_64 6.0-1.el6 base 149 k

Transaction Summary
=====
Install 1 Package(s)
Upgrade 0 Package(s)

Total download size: 149 k
Installed size: 313 k
Is this ok [y/N]: y
Downloading Packages:
unzip-6.0-1.el6.x86_64.rpm | 149 kB | 00:00
Running rpm_check_debug
Running Transaction Test
Transaction Test Succeeded
Running Transaction
Installing : unzip-6.0-1.el6.x86_64 1/1

Installed:
unzip.x86_64 0:6.0-1.el6

Complete!
```

2.3 Extract the ZIP File

We recommend creating a temporary directory to which you can extract the contents of the ZIP file.

1. Use the `mkdir` command to create a temporary directory (in our case, `cdp-agent`).

```
# mkdir cdp-agent
```

2. Use the `mv` command to move the archive to that directory. Note that Linux file names are case sensitive. Make sure you type the name correctly (in our case, "`r1soft-enterprise-agent-linux64-4.2.0.zip`").

```
# mv r1soft-enterprise-agent-linux64-4.2.0.zip cdp-agent
```

3. Use the `cd` command to go to that directory.

```
# cd cdp-agent
```

4. Use the `unzip` command to extract the files.

```
# unzip r1soft-enterprise-agent-linux64-4.2.0.zip
```

```
[root@centos-server cdp]# unzip cdp-enterprise-agent-linux32.zip
Archive:  cdp-enterprise-agent-linux32.zip
  inflating: Enterprise-README.txt
   creating: deb-linux32/
  inflating: deb-linux32/r1soft-cdp-async-agent-2-6-i386-4.2.0.deb
  inflating: deb-linux32/r1soft-cdp-agent-i386-4.2.0.deb
  inflating: deb-linux32/r1soft-cdp-enterprise-agent-i386-4.2.0.deb
  inflating: deb-linux32/r1soft-setup-i386-4.2.0.deb
   creating: rpm-linux32/
  inflating: rpm-linux32/r1soft-cdp-enterprise-agent-4.2.0.i386.rpm
  inflating: rpm-linux32/r1soft-cdp-agent-4.2.0.i386.rpm
  inflating: rpm-linux32/r1soft-cdp-async-agent-2-6-4.2.0.i386.rpm
  inflating: rpm-linux32/r1soft-setup-4.2.0.i386.rpm
```

2.4 Install the Package



Notice

You must be a Linux root user to install CDP Agent.

The archive you have extracted contains two folders: one with `.deb` packages (in our case, "`deb-linux64`") and one with `.rpm` packages ("`rpm-linux64`"). On RedHat and CentOS, select the

.rpm package.

Each folder contains a set of CDP components:

- r1soft-setup
- r1soft-cdp-enterprise-agent
- r1soft-cdp-agent
- r1soft-cdp-async-agent-2-6

You will need to install all of them in one step. Use the `cd` command to go to the folder with the packages (in our case, `rpm-linux64`) and run the following command:

RPM 32-bit (x86) / RPM 64-bit (x86_64)

```
rpm -i *.rpm
```

```
[root@centos-server rpm-linux64]# rpm -i *.rpm
/etc/init.d/cdp-agent stop: cdp (no pid file) not running
Attempting to get a kernel module from 'krnlbld.r1soft.com'

No binary module was found for your kernel. The kernel headers will be required
to build a module. See '/usr/bin/r1soft-setup --help' for more information
/etc/init.d/cdp-agent start: cdp started
```

3. Install CDP Linux Device Driver

CDP Device Driver is a proprietary, loadable Linux kernel module distributed by R1Soft. It is loadable at run-time without restarting Linux, and you do not need to recompile your Linux kernel to use it. R1Soft does not provide prebuilt modules for the popular kernels anymore, so you will have to compile the module from source.



Notice

You need to have loadable modules enabled as a feature in your kernel, and this is standard on all popular Linux distributions.

3.1 Compiling CDP Kernel Module Against Kernel Headers or Kernel Source Tree

Using a pre-built binary module package is not possible anymore. You will have to compile this module against kernel headers or a kernel source tree. We are not always able to compile kernel modules from kernel-devel packages supplied by most major Linux distributions. In some cases, packages are missing header files (broken), or the packages have been stripped of information

that any device driver would need to compile a kernel module. In these cases, we can build using your installed kernel-devel package on your Linux server, as r1soft-setup will obtain the missing information it needs to compile a module from your running kernel.

In order for kernel module compilation to work, you should have Internet connectivity directly from the Linux server you are installing CDP on, to TCP port HTTPS (443), on the host `krnlbld.r1soft.com`.

You can test connectivity with the following command (this may take a minute):

```
# r1soft-setup --test-connection
```

3.2 Install Kernel Sources

If you are using an unmodified kernel provided by CentOS installer, install the kernel-devel package:

```
# yum install kernel-devel
```

```
[root@centos-server ~]# yum install kernel-devel
Loaded plugins: fastestmirror
Determining fastest mirrors
 * base: mirror.karneval.cz
 * extras: mirror.karneval.cz
 * updates: mirror.karneval.cz
base | 3.7 kB | 00:00
extras | 3.5 kB | 00:00
r1soft | 951 B | 00:00
updates | 3.5 kB | 00:00
updates/primary_db | 2.2 MB | 00:12
Setting up Install Process
Resolving Dependencies
--> Running transaction check
--> Package kernel-devel.x86_64 0:2.6.32-220.7.1.el6 set to be installed
--> Finished Dependency Resolution

Dependencies Resolved

=====
Package Arch Version Repository Size
=====
Installing:
kernel-devel x86_64 2.6.32-220.7.1.el6 updates 7.3 M

Transaction Summary
-----
Install 1 Package(s)
Upgrade 0 Package(s)

Total download size: 7.3 M
Installed size: 23 M
Is this ok [y/N]:
```

3.3 Verify that the Source Matches Your Running Kernel

Sometimes, the kernel-devel package is newer than the installed and running kernel. If the kernel-devel is too old and not found, please follow the instructions on how to setup access to older yum packages as documented [here](#).

4.4 Build the CDP Kernel Module Online (direct Internet connection to R1Soft build server)

To attempt to build the kernel module, run the following command (this may take several minutes):

```
# r1soft-setup --get-module
```

```
[root@centos-server ~]# r1soft-setup --get-module
Checking for binary module
Waiting |
No binary module found
Gathering kernel information
Gathering kernel information complete.
Creating kernel headers package
Checking '/lib/modules/2.6.32-220.4.1.el6.x86_64/source/' for kernel headers
Found headers in '/lib/modules/2.6.32-220.4.1.el6.x86_64/source/'
Compressing...
uploading kernel package                               99% 5799KB 485.5KB/s  00:00 ETA
Starting module build...
Complete.
Saving kernel module to '/lib/modules/r1soft/hcpdriver-cki-2.6.32-220.4.1.el6.x86_64.ko'
Kernel module is now installed.
Use '/etc/init.d/cdp-agent restart' to load the new driver
```

If module has been compiled and installed successfully, you will see an output similar to the following:

```
Saving kernel module to '/lib/modules/r1soft/hcpdriver-cki-2.6.32-220.4.1.el6.x86_64.ko'
Kernel module is now installed.
Use '/etc/init.d/cdp-agent restart' to load the new driver
```

3.5 Build the CDP Kernel Module Offline (without direct Internet connection to R1Soft build server)

If there is no direct Internet connection between your CDP server and R1Soft build server, it is still possible to compile the kernel module. In this case, this will be tree-step process. First, you will have to create tarball file with the kernel headers. When you should copy this tarball file from the server to some other computer which has Internet connection to R1Soft build server. From this computer you should upload the tarball to the R1Soft build server and wait for the compilation to finish. When it is finished, you should download binary module and copy it back to the CDP server. Start with executing the following command:

```
# r1soft-setup --no-binary --kernel-dir /usr/src/kernels/YOUR_KERNEL_TREE
--tarball-only /tmp/kernel-headers-for-r1soft.tar.gz
```

After running this command, you will see:

```
# r1soft-setup --no-binary --kernel-dir /usr/src/kernels/2.6.32-220.4.1.el6.x86_64
--tarball-only /tmp/kernel-headers-for-r1soft.tar.gz
Gathering kernel information
Gathering kernel information complete.
Creating kernel headers package
Checking '/usr/src/kernels/2.6.32-220.4.1.el6.x86_64' for kernel headers
Found headers in '/usr/src/kernels/2.6.32-220.4.1.el6.x86_64'
Compressing...
Header package created '/tmp/kernel-headers-for-r1soft.tar.gz'
visit https://krnlbld.r1soft.com/ to do an offline module build
After it is complete, you will need to copy the module to /lib/modules/r1soft
```

```
[root@centos-server ~]# r1soft-setup --no-binary --kernel-dir /usr/src/kernels/2.6.32-220.4.1.el6.x86_64 --tarball-only
/tmp/kernel-headers-for-r1soft.tar.gz
Gathering kernel information
Gathering kernel information complete.
Creating kernel headers package
Checking '/usr/src/kernels/2.6.32-220.4.1.el6.x86_64' for kernel headers
Found headers in '/usr/src/kernels/2.6.32-220.4.1.el6.x86_64'
Compressing...
Header package created '/tmp/kernel-headers-for-r1soft.tar.gz'
visit https://krnlbld.r1soft.com/ to do an offline module build
After it is complete, you will need to copy the module to /lib/modules/r1soft
```

Last Step

- Copy the generated `tar.gz` file and paste it to a computer with Internet access.
- Go to <https://krnlbld.r1soft.com/> and upload the `.tar.gz` file to build a kernel module.
- After the build, you will download a kernel module.
- Copy this module and paste it to your Linux Server and the folder `/lib/modules/r1soft`.
- Restart the Server (`/etc/init.d/cdp-agent restart`).