Solved Issue with Restoring a Drive

Symptom

Performing a restore of a drive to an alternate location is not successful when a user selects an entire disk in the "Browse Recovery Point" window, for example, `C:`.

Resolution

The issue has been corrected in CDP 4.2.0. A disk can now be restored to an alternate location without problems.

Related Articles

Page: Restoring Files (CDP) Labels: standard_edition, enterprise_edition, advanced_edition, restore, recovery_points

Page: Restoring an MS SQL Database (CDP) Labels: standard_edition, enterprise_edition, advanced_edition, recovery_points, restore

Page: Restoring a Microsoft 2007 Exchange Storage Group (Version Before 4.2.0) (CDP) Labels: enterprise_edition, standard_edition, advanced_edition, recovery_points, restore

Page: Restoring a Microsoft Exchange 2010 Mailbox (Version Before 4.2.0) (CDP) Labels: enterprise_edition, recovery_points, restore

Page: Restoring VHDs (CDP) Labels: vhd_hyper-v_explorer, recovery_points, restore

Page: Restoring from Archive Points (CDP) Labels: enterprise_edition, advanced_edition, restore, archive_points

Page: Solved Issue with Missing Files in the Files Restore View (CDP) Labels: restore

Page: Solved Issue with File Restore (CDP) Labels: restore

Page: Solved Issue with Restoring Many Files (CDP) Labels: restore

Page: Solved Issue with Restoring a Drive (CDP) Labels: restore

Page: Restoring a Regular Linux Account (CDP) Labels: standard_edition, enterprise_edition, advanced_edition, restore, recovery_points