Assigning Backups to a Different Disk Safe

Question

I would like to have a weekly "replication" to another location as a sort of "data bunker." Is there any way to create a weekly backup and have it go to a disk safe on a different volume than the other scheduled backups?

Solution

This is not possible in CDP 2.0. However, this can be accomplished with our version 3.x and 4.x product. Simply create a new Disk Safe in the new location and assign it to the existing Agent, then create a new Policy and assign the Agent and new Disk Safe.

Related Articles

Page: BMR of a Citrix Xen 6.0 paravirtualized VM (Knowledge Base) Labels: bare-metal_restore_3, disk_safe_3, partition_3, file_system_3, bmr_3, citrix_3, xen_3, pv_3, hvm_3

Page: Setting Permissions on SSHFS File System (Knowledge Base) Labels: disk_safe_3, troubleshoot_3

Page: Assigning Backups to a Different Disk Safe (Knowledge Base) Labels: disk_safe_3

Page: Error - Caused by Java SQL SQLException Database Is Locked (Knowledge Base) Labels: nfs_3, disk_safe_3, troubleshoot_3

Page: Error - Could Not Create Disk Safe Directory (Knowledge Base) Labels: disk_safe_3, troubleshoot_3, cdp_server_3

Page: Error - Location Does Not Contain a Valid Disk Safe (Knowledge Base) Labels: disk_safe_3, troubleshoot_3

Page: Using Two Policies per Agent (Knowledge Base) Labels: disk_safe_3, policy_3, agent_3, troubleshoot_3, volumes_3

Page: Error - Linux cdp agent fails with "Floating Point Exception" (Knowledge Base) Labels: nfs_3, disk_safe_3, troubleshoot_3