

Uninstalling Agent on Linux

The uninstall program first stops the CDP Agent. You may be asked to confirm the file removals. Information about the uninstallation is displayed on the screen. To remove the entire R1Soft CDP Agent and all of its packages from your computer, follow the below steps.



Notice

The uninstallation process is different depending on whether you use an RPM/YUM (RHE/CentOS/Fedora/Suse/Mandriva) or a DEB/APT (Debian/Ubuntu) Linux distribution.

[RPM/YUM-based Installations](#) | [DEB/APT-based Installations](#)

RPM/YUM-based Installations

Type the removal command and press <Enter>.

```
rpm -e r1soft-cdp-enterprise-agent r1soft-cdp-agent r1soft-cdp-async-agent-2-6 r1soft-setup
```

```
[root@centos-server ~]# rpm -e r1soft-cdp-enterprise-agent r1soft-cdp-agent r1soft-cdp-async-agent-2-6 r1soft-setup
/etc/init.d/cdp-agent stop: cdp stopped
[root@centos-server ~]#
```

Or:

```
yum remove r1soft-cdp-enterprise-agent r1soft-cdp-agent r1soft-cdp-async-agent-2-6 r1soft-setup
```

```
[root@centos-server ~]# yum remove r1soft-cdp-enterprise-agent r1soft-cdp-agent r1soft-cdp-async-agent-2-6 r1soft-setup
Loaded plugins: fastestmirror
Setting up Remove Process
Resolving Dependencies
--> Running transaction check
---> Package r1soft-cdp-agent.x86_64 0:3.18.1-16225 set to be erased
---> Package r1soft-cdp-async-agent-2-6.x86_64 0:3.18.1-16225 set to be erased
---> Package r1soft-cdp-enterprise-agent.x86_64 0:3.18.1-16225 set to be erased
---> Package r1soft-setup.x86_64 0:3.18.1-16225 set to be erased
--> Finished Dependency Resolution

Dependencies Resolved

=====
Package                               Arch          Version          Repository        Size
=====
Removing:
r1soft-cdp-agent                       x86_64        3.18.1-16225    @r1soft           20 M
r1soft-cdp-async-agent-2-6             x86_64        3.18.1-16225    @r1soft           41 M
r1soft-cdp-enterprise-agent            x86_64        3.18.1-16225    @r1soft           0.0
r1soft-setup                            x86_64        3.18.1-16225    @r1soft           2.4 M

Transaction Summary
=====
Remove      4 Package(s)
Reinstall   0 Package(s)
Downgrade   0 Package(s)

Is this ok [y/N]: █
```

Enter "Y" and press <Enter> to confirm the uninstallation.

```
Is this ok [y/N]: y
Downloading Packages:
Running rpm_check_debug
Running Transaction Test
Transaction Test Succeeded
Running Transaction
Erasing      : r1soft-cdp-enterprise-agent-3.18.1-16225.x86_64           1/4
Erasing      : r1soft-cdp-agent-3.18.1-16225.x86_64                    2/4
/etc/init.d/cdp-agent stop: cdp stopped
Erasing      : r1soft-setup-3.18.1-16225.x86_64                        3/4
Erasing      : r1soft-cdp-async-agent-2-6-3.18.1-16225.x86_64          4/4

Removed:
r1soft-cdp-agent.x86_64 0:3.18.1-16225          r1soft-cdp-async-agent-2-6.x86_64 0:3.18.1-16225
r1soft-cdp-enterprise-agent.x86_64 0:3.18.1-16225  r1soft-setup.x86_64 0:3.18.1-16225

Complete!
```

DEB/APT-based Installations

Type the removal command and press <Enter>.

```
apt-get remove r1soft-cdp-enterprise-agent r1soft-cdp-agent r1soft-cdp-async-agent-2-6 r1soft-setup
```

Enter "Y" and press <Enter> to confirm the uninstallation.



Tip

"Yes" is the default answer. To select it, press <Enter>.

```

root@debian-server:~# apt-get remove r1soft-cdp-enterprise-agent r1soft-cdp-agent r1soft-cdp-async-agent-2-6 r1soft-setup
Reading package lists... Done
Building dependency tree
Reading state information... Done
The following packages will be REMOVED:
  r1soft-cdp-agent r1soft-cdp-async-agent-2-6 r1soft-cdp-enterprise-agent r1soft-setup
0 upgraded, 0 newly installed, 4 to remove and 37 not upgraded.
After this operation, 0 B of additional disk space will be used.
Do you want to continue [Y/n]?
(Reading database ... 25554 files and directories currently installed.)
Removing r1soft-cdp-enterprise-agent ...
Removing r1soft-cdp-async-agent-2-6 ...
Removing r1soft-cdp-agent ...
/etc/init.d/cdp-agent stop: cdp stopped
Removing r1soft-setup ...
Processing triggers for nan-db ...
root@debian-server:~# █

```

Or:

```
aptitude remove r1soft-cdp-enterprise-agent r1soft-cdp-agent r1soft-cdp-async-agent-2-6 r1soft-setup
```

```

root@debian-server:~# aptitude remove r1soft-cdp-enterprise-agent r1soft-cdp-agent r1soft-cdp-async-agent-2-6 r1soft-setup
The following packages will be REMOVED:
  r1soft-cdp-agent r1soft-cdp-async-agent-2-6 r1soft-cdp-enterprise-agent r1soft-setup
0 packages upgraded, 0 newly installed, 4 to remove and 37 not upgraded.
Need to get 0 B of archives. After unpacking 0 B will be used.
(Reading database ... 25554 files and directories currently installed.)
Removing r1soft-cdp-enterprise-agent ...
Removing r1soft-cdp-async-agent-2-6 ...
Removing r1soft-cdp-agent ...
/etc/init.d/cdp-agent stop: cdp stopped
Removing r1soft-setup ...
Processing triggers for nan-db ...

```

Or:

```
dpkg -r r1soft-cdp-enterprise-agent r1soft-cdp-agent r1soft-cdp-async-agent-2-6 r1soft-setup
```

```

root@debian-server:~# dpkg -r r1soft-cdp-enterprise-agent r1soft-cdp-agent r1soft-cdp-async-agent-2-6 r1soft-setup
(Reading database ... 25554 files and directories currently installed.)
Removing r1soft-cdp-enterprise-agent ...
Removing r1soft-cdp-async-agent-2-6 ...
Removing r1soft-cdp-agent ...
/etc/init.d/cdp-agent stop: cdp stopped
Removing r1soft-setup ...
Processing triggers for nan-db ...
root@debian-server:~# █

```

To delete all archives and configurations:

Substitute "purge" for "remove."

```

root@debian-server:~# aptitude purge r1soft-cdp-enterprise-agent r1soft-cdp-agent r1soft-cdp-async-agent-2-6 r1soft-setup
The following packages will be REMOVED:
  r1soft-cdp-agent(p) r1soft-cdp-async-agent-2-6{p} r1soft-cdp-enterprise-agent{p} r1soft-setup(p)
0 packages upgraded, 0 newly installed, 4 to remove and 37 not upgraded.
Need to get 0 B of archives. After unpacking 0 B will be used.
Do you want to continue? [Y/n/?] Y
(Reading database ... 25554 files and directories currently installed.)
Removing r1soft-cdp-enterprise-agent ...
Purging configuration files for r1soft-cdp-enterprise-agent ...
Removing r1soft-cdp-async-agent-2-6 ...
Purging configuration files for r1soft-cdp-async-agent-2-6 ...
Removing r1soft-cdp-agent ...
/etc/init.d/cdp-agent stop: cdp stopped
Purging configuration files for r1soft-cdp-agent ...
dpkg: warning: while removing r1soft-cdp-agent, directory '/usr/sbin/r1soft/conf' not empty so not removed.
dpkg: warning: while removing r1soft-cdp-agent, directory '/usr/sbin/r1soft' not empty so not removed.
Removing r1soft-setup ...
Purging configuration files for r1soft-setup ...
Processing triggers for nan-db ...

```

Or "`-P`" for "`-r`" in the `dpkg` command.

```
root@debian-server:~# dpkg -P r1soft-cdp-enterprise-agent r1soft-cdp-agent r1soft-cdp-async-agent-2-6 r1soft-setup
(Reading database ... 25554 files and directories currently installed.)
Removing r1soft-cdp-enterprise-agent ...
Purging configuration files for r1soft-cdp-enterprise-agent ...
Removing r1soft-cdp-async-agent-2-6 ...
Purging configuration files for r1soft-cdp-async-agent-2-6 ...
Removing r1soft-cdp-agent ...
/etc/init.d/cdp-agent stop: cdp stopped
Purging configuration files for r1soft-cdp-agent ...
dpkg: warning: while removing r1soft-cdp-agent, directory '/usr/sbin/r1soft/conf' not empty so not removed.
dpkg: warning: while removing r1soft-cdp-agent, directory '/usr/sbin/r1soft' not empty so not removed.
Removing r1soft-setup ...
Purging configuration files for r1soft-setup ...
Processing triggers for man-db ...
```



Note

None of the above commands remove the `/usr/sbin/r1soft/conf` directory. It remains in the system for future use. If necessary, you can delete it manually as shown in the following screenshot, using the "`rm -rf`" command.

```
root@debian-server:~# rm -rf /usr/sbin/r1soft/conf
root@debian-server:~#
```

Once the uninstallation process is complete, the R1Soft CDP Agent full stack of installed packages is removed from your computer.